

WIRELESS MICROPHONE SYSTEM

# Live Star UHF Wireless Microphone System

Fixed frequency wireless microphone system

# LIVE STAR UX3

Fixed frequency wireless microphone systems with handheld transmitters. UX 3 systems are available in 4 fixed frequencies 626.63 MHz, 630.4 MHz, 863.425 MHz and 864.9 MHz. Simple setup, LED backlight display, RF and AF indicators, volume control, dynamic cardioid capsule, balanced XLR and unbalanced 6,3mm TS jack outputs. iLive UX 3 is perfect budget microphone system for schools or small meeting rooms.

Technical Specifications	UX 3
Carrier frequency	626,63 MHz & 630,4 MHz 863,425 MHz & 864,9 MHz
Power supply	12 - 16 V DC, 400mA
Outputs	Balanced XLR, unbalanced 6,3 mm TS Jack
Modulation	FM
Frequency response	40 Hz - 18 kHz
THD	0,5 %
Signal / noise ratio	85 dB
Antenna connector	BNC
Max. audio output level	-6 dBu (balanced), -12 dBu (unbalanced)
Transmitter's power	10 mW
Working range	60 m (Note: actual range depends on RF signal absorption and interference )
Capsule polar pattern	Cardioid
Battery	2 x 1,5 V AA alkaline battery
Material	Plastic
Weight	1,4 kg
Receivers dimensions	42 mm x 200 mm x 150 mm

